

No Utility Bills Inc.

www.noutilitybills.com

Tel: (780)628-4835

#301 Lyall Subdivision, County of Athabasca, AB, Canada
VIEWINGS BY APPOINTMENT ONLY!

HeatMaster GS Series EPA Outdoor Wood Boilers

Industry Leading Efficiency & Emissions

Exceeds government regulations by over 75%.

High Efficiency Combustion Chamber Design:

The horseshoe refractory design creates the cleanest, hottest burn (up to 2000°F).

Easy Plumbing & Service Access: Insulated, hinged rear door allows wide open access to the fan & pumps.

Burn Sight Glass: Check the burn process without opening the doors and disrupting the fire.

Safety Door Latch: Latch catches the door so it doesn't swing open and expose you to excessive heat.

EZ Clean Handle: Just a few pulls on the handle, then walk away!



Specifications	GS 100	GS 200	GS 400
List Price Less Freight			
Sale Price Less Freight			
Estimated F.O.B. NUB Yard			
Length	57"	71"	85"
Width	38"	51"	51"
Height	78"	88"	91"
Insulated Chimney	6"	6"	8"
Door Size	16" X 16"	20" X 20"	20" X 20"
Weight	1086 LB	1802 LB	2420 LB
Water Capacity	90 US Gal	195 US Gal	260 US Gal
Wood / Firebox Length	20"	30"	42"
Firebox (W" x L" x H")	19x20x30	28x30x36	30x42x40
EPA Test BTU Output *8 hr*	42,772	111,315	180,409
Maximum BTU Output	120,000	232,000	340,000
Inlets & Outlets	1 Each 1"	2 Each 1"	2 Each 1-1/2"
Btu's varies according to fuel type, quality and moisture content. Delivery, Installation Materials and Installation Labor Are Not Included! These Services Can Be Provided For An Additional Cost. All specifications are subject to change and / or corrections without notice.!!			

Modern Finish: The smooth finish is easy to wipe down and keep clean.

Draft Induction Fan: Draws air through the furnace to maintain gasification while keeping airways open.

Rounded Firebox: Increases strength with fewer welds.

Easy to Read Water Level Gauge

High R Value Multi-layer Insulation

Control Panel: Programmed for an efficient and even burn. The cover protects components from the elements

Loading Switch: Activates fan for reduced smoke when loading.

EZ Clean Handle: Clean the heat exchange tubes quickly and easily and reduce time for maintenance. No brushing tubes or scraping creosote!

Low Maintenance, High Efficiency Heat Exchange Tubes: The vertical heat exchange tubes keep ash and creosote from collecting and blocking the tube. Spirals in the tubes ensure the highest efficiency.

Lifetime Limited Warranty: HeatMaster's industry leading Lifetime Limited Warranty proves our commitment to quality.

