

No Utility Bills Inc.

www.noutilitybills.com

Tel: (780)628-4835

#301 Lyall Subdivision, County of Athabasca, AB, Canada

VIEWINGS BY APPOINTMENT ONLY!

The PSG Furnace Product Line



Model	Caddy	Caddy Max
List Price From *		
Sale Price From *		
Type of fuel(s)	Wood, Electric & Fuel Oil	Wood, Electric & Fuel Oil
Certified add-on furnace	Yes	No
Stand alone furnace	Yes - Optional	Yes
Maximum input capacity	140,000 (42 kW)	180,000 (53 kW)
Maximum output capacity	106,400 BTU (31,2 kW)	137,970 BTU (41 kW)
Average Output capacity	69,160 BTU (20,3 kW)	89,680 BTU (27 kW)
Maximum output capacity * EPA	52,000 BTU (15,2 kW)	N/A
Loading capacity	Up to 70 lbs (32 kg)	Up to 90 lbs (41 kg)
Recommended element	18 kW	20 kW
Optional electric element	15 kW, 20 kW, 25 kW	20 kW, 25 kW
Optional oil burner input	91,000 BTU (27 kW)	120,000 BTU
Exterior dimensions	26"W x 47"D x 48"H	30"W x 62"D x 50"H
Chimney diameter	6" - 7" Wood/Oil Combo With Barometric Damper	6" - 7" Wood/Oil Combo With Barometric Damper
*Minimum Chimney	Not Stated	Not Stated
Firebox dimensions	12"W x 24"D x 16"H	20.375"W x 26.25"D x 14.5"H
Maximum log length	21.5"	25"
Door opening dimensions	13.75"W x 10"H	15.625"W x 10"H
Weight	445 (202 kg) - 560 lbs (254 kg)	650 lbs (295 kg)
Blower	Stand alone * 1/3 HP 4 speed Direct drive, 1300 cfm	1/2 HP 4 speed Direct drive, 1780 cfm
Supply Plenum Size	24-9/16" x 28-3/4"	32-1/4" x 25-1/2"
Return Plenum Size	15-3/4" x 24-3/4"	18" x 20"
Filter Size	14" x 25" x 1"	16" x 20" x 1"
Duct Clearance	6" For First 6' & 1" After	6" For First 6' & 1" After
Test standard - emissions	EPA / CSAB415.1	CSAB415.1
Efficiency	Oil - 82% / Wood - 73 %	Oil - 83% / Wood - 77 %
Test standard - safety	Can CSA B366.1-M91, CSAB212-93, UL391 3e Ed. rev. 1999	

* Specifications & Prices subject to change without notice!

See website and product manuals for full specifications!

No Utility Bills Inc.

www.noutilitybills.com

Tel: (780)628-4835

#301 Lyall Subdivision, County of Athabasca, AB, Canada

VIEWINGS BY APPOINTMENT ONLY!

The PSG Furnace Product Line



Model	Caddy Alterna	Mini Caddy
List Price From *		
Sale Price From *		
Type of fuel(s)	Wood & Biomass Pellets & Electric	Wood & Electric
Certified add-on furnace	No	No
Stand alone furnace	Yes	Yes
Maximum input capacity	120,000 BTU (36 kW)	75,000 BTU (21.6 kW)
Maximum output capacity	108,000 BTU (32 kW)	63,750 BTU (18.7 kW)
Average Output capacity	N/A	41,440 BTU (12.2 kW)
Maximum output capacity * EPA	N/A	25,500 BTU (7.5 kW)
Loading capacity	Up to 240 pounds (109 kg)	Up to 40 pounds (18 kg)
Recommended element	15 kW or 20 kW	11 kW
Optional electric element	15 kW, 20 kW	N/A
Optional oil burner input	N/A	N/A
Exterior dimensions	26.25"W x 5.25"D x 47"H	23.25"W x 39.75"D x 45.625"H
Chimney diameter	4"	6" With Barometric Damper
*Minimum Chimney	N/A	Not Stated
Firebox dimensions	N/A	14"W x 19 3/8"D x 12"H
Maximum log length	N/A	18-3/8"
Door opening dimensions	N/A	13 1/2"W x 9 5/8"H
Weight	500 lbs (227 kg)	405 lbs (184 kg)
Blower	1/2 HP 4 speed Direct drive, 1050 cfm	1/4 HP Direct-drive (4 speeds)
Supply Plenum Size	22" x 22"	12" x 12"
Return Plenum Size	21-1/4" x 16-1/4"	22" x 13-3/8"
Filter Size	16" 20" x 1"	15" 20" x 1"
Duct Clearance	2" For First 5' & 1" After	3" For First 6' & 1" After
Test standard - emissions	EPA / CSAB415.1	EPA / CSAB415.1
Efficiency	Wood Pellets 90%	N/A
Test standard - safety	CAN/CSA B366.1, UL 391, CAN/CSA C22.2 no 236, UL 1995, ASTM E1509, ULC/ORD-C1482	CAN CSA B366.1-M91, CSA C22.2 No. 236, UL 1995, UL391 3e Ed. rev. 1999

* Specifications & Prices subject to change without notice!

See website and product manuals for full specifications!